TOYOTA (USA / CAN) TUNDRA TUNDRA 4.7 V8 32V 2WD (USA) UCK50/51/52 (2007-2009)



ENGINE 2UZ-FE Capacity: 7,1 liter (Dry fill), Capacity: 6,2 liter (Service fill), Filter capacity: 0,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Presteza MSP 5W-30			
		ê	

Change every 5000 miles/ 6 months

DIFFERENTIAL REAR Capacity: 4,05-4,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	
Check every 15000 miles/ 18 months	
USE	CLIMATE

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	
Change every 15000 miles/ 18 months	

TRANSMISSION AUTOMATIC A340E 4/1 Capacity: 10,5 liter (Dry fill), Capacity: 11,1 liter (Dry fill with towing package), Capacity: 3 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 30000 miles/ 36 months

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	

Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months

TOYOTA (USA / CAN) TUNDRA TUNDRA 4.7 V8 32V 2WD (USA) UCK50/51/52 (2007-2009)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check avery 5000 miles (6 months		

Check every 5000 miles/ 6 months

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
		0

Check every 5000 miles/ 6 months

COOLING SYSTEM Capacity: 9,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.