Change every 15000 km/ 12 months

VAUXHALL ASTRA / BELMONT T85 ASTRA / BELMONT 1.4I (44 KW) (1989-1991)



ENGINE C14NZ Capacity: 3 liter, Filter capacity: 0,25 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Bi-Turbo 20W-50			
Change every 15000 km/ 12 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Helar 0W-40	Emperol 5W-40	Emperol Racing 10W-60	

TRANSAXLE MANUAL 4/1 Capacity: 1,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Check every 15000 km/ 12 months		

TRANSAXLE MANUAL 5/1 Capacity: 1,85 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Check every 15000 km/ 12 months	•	,

HYDRAULIC BRAKE SYSTEM Capacity: 0,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 12 months			

VAUXHALL ASTRA / BELMONT T85 ASTRA / BELMONT 1.4I (44 KW) (1989-1991)



COOLING SYSTEM Capacity: 6,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.