VAUXHALL ASTRA / BELMONT T85 ASTRA / BELMONT 1.8S (62 KW) (1987-1991)



USE CLIMATE Normal Mediterranean PRODUCT RECOMMENDATION 1 Image of the second s	Normal PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 15000 km/ 12 months use Normal	CLIMATE	an
PRODUCT RECOMMENDATION 1 Image of the second se	PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 15000 km/ 12 months USE Normal	CLIMATE	an
Bi-Turbo 20W-50 Image every 15000 km/ 12 months Change every 15000 km/ 12 months CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Helar 0W-40 Emperol 5W-40 Change every 15000 km/ 12 months Emperol 5W-40 USE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean	Bi-Turbo 20W-50 Change every 15000 km/ 12 months use Normal		
Change every 15000 km/ 12 months USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Helar 0W-40 Emperol 5W-40 Change every 15000 km/ 12 months Emperol 5W-40 USE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	Change every 15000 km/ 12 months use Normal		
USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Helar 0W-40 Emperol 5W-40 Change every 15000 km/ 12 months Emperol 5W-40 USE CLIMATE Severe CLIMATE PRODUCT RECOMMENDATION 1 Moderate	use Normal		
NormalModeratePRODUCT RECOMMENDATION 1PRODUCT RECOMMENDATION 2PRODUCT RECOMMENDATION 3Helar 0W-40Emperol 5W-40Emperol Racing 10W-60Change every 15000 km/ 12 monthsCLIMATESevereCLIMATEPRODUCT RECOMMENDATION 1PRODUCT RECOMMENDATION 1	Normal		
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 Change every 15000 km/ 12 months CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 Image: Climate Action 1			
Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 Change every 15000 km/ 12 months CLIMATE USE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 Image: Climate		Moderate	
Change every 15000 km/ 12 months USE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 Image: Climate	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2 PRODUCT RECOM	IMENDATION 3
USE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1	Helar 0W-40	Emperol 5W-40 Emperol Rad	cing 10W-60
Severe Mediterranean PRODUCT RECOMMENDATION 1 Image: Comparison of the second	Change every 15000 km/ 12 months		
PRODUCT RECOMMENDATION 1	USE	CLIMATE	
	Severe	Mediterranea	an .
	PRODUCT RECOMMENDATION 1		
	Bi-Turbo 20W-50		
Change every 15000 km/ 6 months	Change every 15000 km/ 6 months		
USE CLIMATE	USE	CLIMATE	
Severe Moderate	Severe	Moderate	
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2 PRODUCT RECOM	IMENDATION 3
Helar 0W-40Emperol 5W-40Emperol Racing 10W-60	Helar 0W-40	Emperol 5W-40 Emperol Rad	cing 10W-60
Change every 15000 km/ 6 months	Character average 4E000 kms/ Conservation		
	Change every 15000 km/ 6 months		

TRANSAXLE AUTOMATIC 3/1 Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Check every 15000 km/ 12 months, change every 60000 km/ 48 months

TRANSAXLE MANUAL 5/1 Capacity: 2,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube GL-4 80W		
Oh		· · · ·	

Check every 15000 km/ 12 months

VAUXHALL ASTRA / BELMONT T85 ASTRA / BELMONT 1.8S (62 KW) (1987-1991)



HYDRAULIC BRAKE SYSTEM Capacity: 0,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 12 months

COOLING SYSTEM Capacity: 7,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.