## VAUXHALL CARLTON V87 CARLTON 2.0I (90 KW) (1986-1988)



Change every 15000 km/ 12 months  JSE  Normal  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  PREDICT RECOMMENDATION 2  PREDICT RECOMMENDATION 2  Emperol 5W-40  Change every 15000 km/ 12 months  JSE  CLI  Change every 15000 km/ 12 months  JSE  CRODUCT RECOMMENDATION 1  BI-Turbo 20W-50  Change every 15000 km/ 6 months	Mediterranean
Normal  PRODUCT RECOMMENDATION 1  Helar 0W-40  Change every 15000 km/ 12 months  USE  Severe  PRODUCT RECOMMENDATION 2  Emperol 5W-40  Er  CLange every 15000 km/ 12 months  CLange every 15000 km/ 6 months	
Change every 15000 km/ 12 months  USE  Normal  PRODUCT RECOMMENDATION 1  Helar 0W-40  Change every 15000 km/ 12 months  USE  Severe  PRODUCT RECOMMENDATION 1  Bi-Turbo 20W-50  Change every 15000 km/ 6 months	
Normal  PRODUCT RECOMMENDATION 1  Helar 0W-40  Change every 15000 km/ 12 months  USE  Severe  PRODUCT RECOMMENDATION 2  Emperol 5W-40  Er  CLI  Severe  MC  PRODUCT RECOMMENDATION 1  Bi-Turbo 20W-50  Change every 15000 km/ 6 months	
Normal  PRODUCT RECOMMENDATION 1  Helar 0W-40  Change every 15000 km/ 12 months  USE  Severe  PRODUCT RECOMMENDATION 2  Emperol 5W-40  En  CLI  Severe  Mo  PRODUCT RECOMMENDATION 1  Bi-Turbo 20W-50  Change every 15000 km/ 6 months	
PRODUCT RECOMMENDATION 1 Helar 0W-40 Emperol 5W-40 Er  Change every 15000 km/ 12 months  USE Severe PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50  Change every 15000 km/ 6 months	LIMATE
Helar 0W-40 Emperol 5W-40 Er  Change every 15000 km/ 12 months  USE CLI  Severe Mc  PRODUCT RECOMMENDATION 1  Bi-Turbo 20W-50  Change every 15000 km/ 6 months	/loderate
Change every 15000 km/ 12 months  USE Severe PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50  Change every 15000 km/ 6 months	RODUCT RECOMMENDATION 3
USE Severe More Manage every 15000 km/ 6 months	Emperol Racing 10W-60
Severe  PRODUCT RECOMMENDATION 1  Bi-Turbo 20W-50  Change every 15000 km/ 6 months	
PRODUCT RECOMMENDATION 1  Bi-Turbo 20W-50  Change every 15000 km/ 6 months	LIMATE
Bi-Turbo 20W-50  Change every 15000 km/ 6 months	/lediterranean
Change every 15000 km/ 6 months	
USE CLI	LIMATE
Severe Me	Moderate
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PR	RODUCT RECOMMENDATION 3
Helar 0W-40 Emperol 5W-40 Er	Emperol Racing 10W-60
Change every 15000 km/ 6 months	

Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 15000 km/ 12 months	·

TRANSMISSION AUTOMATIC 4/1 Capacity: 5,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 36 months	

## VAUXHALL CARLTON V87 CARLTON 2.0I (90 KW) (1986-1988)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear TDL 75W-90

Check every 15000 km/ 12 months

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 12 months		

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

COOLING SYSTEM Capacity: 6,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.