## VAUXHALL CAVALIER III J89 CAVALIER 2.0S (1988-1995)



USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 months		·
JSE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Emperol Racing 10W-60
Change every 15000 km/ 12 months		
JSE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Emperol Racing 10W-60
Change every 15000 km/ 6 months	·	·

TRANSAXLE AUTOMATIC 3/1 Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 36 months	

TRANSAXLE MANUAL 4/1 Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Check every 15000 km/ 12 months		·

## **VAUXHALL CAVALIER III J89 CAVALIER 2.0S** (1988-1995)



HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Change every 12 months

POWER STEERING Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

COOLING SYSTEM Capacity: 7 liter (+ automatic transmission/transaxle), Capacity: 7,2 liter (+ manual transmission/transaxle)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Change every 24 months	'	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.