## VAUXHALL MOKKA J13 MOKKA 1.4 TURBO (103 KW) (2014-2016)



<b>ENGINE</b> B14NET (LUJ) Capacity: 4 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Xedoz FE 5W-30

Change every 30000 km/ 12 months

TRANSAXLE AUTOMATIC 6T40/6T45/6T50 6/1 Capacity: 8-8,5 liter (Dry fill), Capacity: 4-6 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			

Check every 12 months/ 30000 km

TRANSAXLE MANUAL M32 6/1 Capacity: 1,9 liter (Dry fill), Capacity: 1,3 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Gear 1081			
Check every 12 months/ 30000 km			

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
	•

## VAUXHALL MOKKA J13 MOKKA 1.4 TURBO (103 KW) (2014-2016)



Coolant SP 15	Coolant SP 15+	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
COOLING SYSTEM		

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.