## VAUXHALL VECTRA B J96 VECTRA B 2.5 V6 (1995-2001)



| ISE                              |                          | CLIMATE                  |
|----------------------------------|--------------------------|--------------------------|
| Normal                           |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1         |                          |                          |
| Bi-Turbo 20W-50                  |                          |                          |
| Change every 15000 km/ 12 months |                          | ,                        |
| USE                              |                          | CLIMATE                  |
| Normal                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40                      | Emperol 5W-40            | Emperol Racing 10W-60    |
| Change every 15000 km/ 12 months |                          | ·                        |
| USE                              |                          | CLIMATE                  |
| Severe                           |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1         |                          |                          |
| Bi-Turbo 20W-50                  |                          |                          |
| Change every 15000 km/ 6 months  |                          | ·                        |
| USE                              |                          | CLIMATE                  |
| Severe                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40                      | Emperol 5W-40            | Emperol Racing 10W-60    |
| Change every 15000 km/ 6 months  |                          |                          |

| TRANSAXLE AUTOMATIC 4/1 Capacity: 3 liter |          |
|---|----------|
| USE                                       | CLIMATE  |
| Normal                                    | Moderate |
| PRODUCT RECOMMENDATION 1                  |          |
| ATF Dexron II-D                           |          |
| Check every 24 months/ 30000 km           |          |

| TRANSAXLE MANUAL 5/1<br>Capacity: 1,8 liter |                          |          |  |
|---|--------------------------|----------|--|
| USE   |                          | CLIMATE  |  |
| Normal                                      |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2 |          |  |
| SP Gear 5015                                | Gearlube GL-4 80W        |          |  |
| Check every 15000 km/ 12 months             | ·                        |          |  |

## VAUXHALL VECTRA B J96 VECTRA B 2.5 V6 (1995-2001)



| HYDRAULIC BRAKE/CLUTCH SYSTE Capacity: 0,4 liter | EM                       |                     |  |
|--|--------------------------|---------------------|--|
| use<br>Normal                                    |                          | climate<br>Moderate |  |
| PRODUCT RECOMMENDATION 1                         | PRODUCT RECOMMENDATION 2 | iwoderate           |  |
| Drauliquid-LV Super DOT 4                        | Drauliquid-S DOT 4       |                     |  |
|  | ·                        |                     |  |

Change every 24 months

| POWER STEERING Capacity: 1,4 liter |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| ATF Dexron II-D                    |          |

| COOLING SYSTEM Capacity: 7,7 liter |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| Coolant -38 Organic NF             |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.