VAUXHALL VECTRA C Z02 VECTRA C 1.9 CDTI DPF (88 KW) (2004-2009)



ENGINE Z19DTL DPF Capacity: 4,3 liter		
use Flexible (max)		climate Moderate
Presteza MSP 5W-30	Helar MSP+ 5W-40	Specialsynth MSP 5W-40

Change every 30000 km/ 12 months

TRANSAXLE MANUAL F40 6/1 Capacity: 2,2 liter		
use Normal		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

HYDRAULIC BRAKE/CLUTCH SYST Capacity: 0,4 liter	EM	
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
		

Check every 30000 km/ 12 months, change every 24 months

POWER STEERING Capacity: 0,7-1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 7 liter, Capacity: 0,5 liter (with 4 zone airconditioning system)				
USE		CLIMATE		
Flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant SP 15	Coolant SP 15+			
Check every 12 months/ 30000 km				

PRODUCT RECOMMENDATION

VAUXHALL VECTRA C Z02 VECTRA C 1.9 CDTI DPF (88 KW) (2004-2009)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.