VAUXHALL VECTRA C Z02 VECTRA C 2.0 DTI 16V (2002-2005)



ENGINE Y20DTH Capacity: 5,5 liter		
use Flexible (max)		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Helar MSP+ 5W-40	Specialsynth MSP 5W-40

Change every 50000 km/ 24 months

TRANSAXLE MANUAL F23 5/1 Capacity: 1,55 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
		•

Change every 24 months

POWER STEERING Capacity: 0,7-1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	

COOLING SYSTEM Capacity: 8,2 liter			
use Flexible (max)		сымате Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Check every 50000 km/ 24 months		·	

VAUXHALL VECTRA C Z02 VECTRA C 2.0 DTI 16V (2002-2005)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.