VAUXHALL VECTRA C Z02 VECTRA C 2.8 V6 TURBO VXR (2006-2009)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40

Change every 30000 km/ 12 months

TRANSAXLE AUTOMATIC AF 40 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Servi	ce fill)
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 80000 km/ 72 months	

TRANSAXLE MANUAL F40 6/1 Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS			
USE		CLIMATE	
Flexible (max)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 30000 km/ 12 months ch	ange every 24 months	<u> </u>	

Check every 30000 km/12 months, change every 24 months

POWER STEERING Capacity: 0,7-1 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

VAUXHALL VECTRA C Z02 VECTRA C 2.8 V6 TURBO VXR (2006-2009)



COOLING SYSTEM Capacity: 7,5 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Check every 12 months/ 30000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.