VAUXHALL ZAFIRA B A05 ZAFIRA B 1.8 (103 KW) (2005-2010)



| ENGINE Z18XER Capacity: 4,5 liter | | | |
|-----------------------------------|--------------------------|--------------------------|--|
| use Normal | | CLIMATE | |
| | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Presteza MSP 5W-30 | Helar MSP+ 5W-40 | Specialsynth MSP 5W-40 | |

Change every 30000 km/ 12 months

| TRANSAXLE AUTOMATIC AF 22 4/1 | | |
|-------------------------------|----|----------|
| USE | CL | IMATE |
| Normal | M | loderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |

| TRANSAXLE MANUAL F17+ 5/1 Capacity: 1,6 liter | | | |
|--|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| SP Gear 1011 | SP Gear 5015 | Syngear TDL 75W-90 | |

| TRANSAXLE SEMI-AUTOMATIC F17 MTA 5/1 Capacity: 1,6 liter | | | |
|--|--------------|---------------------|--|
| use Normal | | climate Moderate | |
| | | | |
| SP Gear 1011 | SP Gear 5015 | Syngear TDL 75W-90 | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM ABS | | | |
|-------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| Check every 30000 km/ 12 months, ch | ange every 24 months | | |

VAUXHALL ZAFIRA B A05 ZAFIRA B 1.8 (103 KW) (2005-2010)



| POWER STEERING | |
|---------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Fluid 3013 | |
| Check every 12 months/ 30000 km | |

| COOLING SYSTEM Capacity: 0-0 liter (Between min an | d max.) | | |
|--|--------------------------|----------|--|
| use Normal | | CLIMATE | |
| | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15 | Coolant SP 15+ | | |
| Check every 12 months/ 30000 km | , | ' | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.