## VAUXHALL ZAFIRA C P12 ZAFIRA C 1.6 TURBO (147 KW) (2013-2015)



<b>ENGINE</b> A16SHT (LWC) Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Xedoz FE 5W-30

Change every 30000 km/ 12 months

TRANSAXLE MANUAL M32 6/1 Capacity: 2,2 liter (Dry fill), Capacity: 2 liter (Service fill)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Gear 1081				
Check every 12 months/ 30000 km				

HYDRAULIC BRAKE SYSTEM			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid-LV Super DOT 4			
Change every 24 months			

COOLING SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant SP 15	Coolant SP 15+			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.