

VOLKSWAGEN (VW) (EU) EOS 1F7 EOS 2.0 16V TFSI (155 KW) (2009-2010)

**ENGINE CCZB**

Capacity: 4,6 liter, Filter capacity: 0,5 liter

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Change every 30000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

*Change every 15000 km/ 12 months***TRANSAXLE MANUAL 02Q 6/1**

Capacity: 2,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

TRANSAXLE SEMI-AUTOMATIC DSG 02E (DQ250) 6/1

Capacity: 7,2 liter (Dry fill), Capacity: 5,2 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		

*Change every 60000 km***HYDRAULIC ACTUATION CONVERTIBLE ROOF**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

VOLKSWAGEN (VW) (EU) EOS 1F7 EOS 2.0 16V TFSI (155 KW) (2009-2010)



HYDRAULIC ACTUATION GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 48 months/ 60000 km

ELECTRO-HYDRAULIC POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 48 months/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.