## VOLKSWAGEN (VW) (EU) GOLF PLUS 5M1 GOLF PLUS 1.4 16V (55 KW) (2005-2006)



ENGINE BCA Capacity: 3,2 liter		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	
Change every 30000 km/ 24 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Helar 0W-40
Change every 15000 km/ 12 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Presteza MSP 5W-30		
Change every 15000 km/ 12 months		

TRANSAXLE MANUAL 0AF 5/1 Capacity: 2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		
Check even 40 menths/ COOOO km			

Check every 48 months/ 60000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 1 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid-LV Super DOT 4				

Change every 24 months

## VOLKSWAGEN (VW) (EU) GOLF PLUS 5M1 GOLF PLUS 1.4 16V (55 KW) (2005-2006)



COOLING SYSTEM Capacity: 5,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 12 EVO			

Check every 48 months/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.