VOLKSWAGEN (VW) (EU) GOLF VII 5G1 GOLF VII 1.6 TDI (77 KW) 4MOTION (2012-



2014)

ENGINE CLHA Capacity: 4,7 liter (Service fill)	
USE	CLIMATE
Extended drain (max)	Moderate
PRODUCT RECOMMENDATION 1	
Helar SP LL-03 5W-30	
Change every 30000 km/ 24 months	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Helar SP LL-03 5W-30	
Change every 15000 km/ 12 months	

ANGLE GEARBOX / TRANSFERB Capacity: 0,9 liter	ox		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

DIFFERENTIAL REAR Capacity: 0,95 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

TRANSAXLE MANUAL 02Q 6/1 Capacity: 2,3 liter (Dry fill), Capacity	y: 2,15 liter (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 24 months/ 30000 km	'	'

PRODUCT RECOMMENDATION

VOLKSWAGEN (VW) (EU) GOLF VII 5G1 GOLF VII 1.6 TDI (77 KW) 4MOTION (2012-



2014)

HALDEX-CLUTCH Capacity: 0,85 liter (Dry fill), Capacity: 0,65	liter (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 6036		
Change every 36 months		

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 1,15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	

Check every 48 months/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.