

# VOLKSWAGEN (VW) (EU) PASSAT 3A

## PASSAT 1.8 (55 KW) (1990-1992)



**ENGINE AAM**  
Capacity: 4 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 2

**Specialsynth MSP 5W-40**

PRODUCT RECOMMENDATION 3

**Emperol 5W-40**

*Change every 15000 km/ 12 months*

**TRANSAXLE MANUAL 5/1**  
Capacity: 2 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

PRODUCT RECOMMENDATION 3

**Syngear 75W-90**

*Check every 15000 km/ 12 months*

### HYDRAULIC BRAKE SYSTEM

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

*Change every 24 months*

### POWER STEERING

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**SP Fluid 3013**

### COOLING SYSTEM

Capacity: 5 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 11**

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*