

# VOLKSWAGEN (VW) (EU) PASSAT 3A

## PASSAT 1.9 DIESEL (1989-1992)

**ENGINE 1Y**

Capacity: 4,5 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Specialsynth MSP 5W-40</b>	<b>Emperol 5W-40</b>	<b>Emperol 10W-40</b>

*Change every 7500 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>Presteza MSP 5W-30</b>		

*Change every 7500 km/ 12 months***TRANSAXLE MANUAL 4/1**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Syngear 75W-90</b>

**HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 24 months***POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

# VOLKSWAGEN (VW) (EU) PASSAT 3A

## PASSAT 1.9 DIESEL (1989-1992)

**COOLING SYSTEM**

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Coolant SP 11***Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*