

VOLKSWAGEN (VW) (EU) PASSAT B8 3G

PASSAT 1.6 TDI (88 KW) (2014-2020)



ENGINE DCXA, DCZA
Capacity: 4,7 liter (Service fill)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30

Change every 15000 km/ 12 months

USE
Flexible (max)

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30

Change every 30000 km/ 24 months

TRANSAXLE MANUAL 02S 6/1
Capacity: 2,3 liter (Dry fill), Capacity: 2,1 liter (Service fill)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

PRODUCT RECOMMENDATION 2

SP Gear 5015

Check every 24 months/ 30000 km

TRANSAXLE SEMI-AUTOMATIC DSG 0CW (DQ200) 7/1
Capacity: 1,7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

PRODUCT RECOMMENDATION 2

SP Gear 5015

HYDRAULIC ACTUATION GEARBOX
Capacity: 0,9 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

VOLKSWAGEN (VW) (EU) PASSAT B8 3G

PASSAT 1.6 TDI (88 KW) (2014-2020)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 1-1,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Check every 48 months/ 60000 km*

COOLING SYSTEM AS OF PRODUCTION DATE 08-07-2019

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.