

# VOLKSWAGEN (VW) (EU) PASSAT CC 357

## PASSAT CC 2.0 TDI (103 KW) 4MOTION

### (2009-2010)



**ENGINE** CBAB, CFFB  
Capacity: 4 liter

| USE                  | CLIMATE  |
|----------------------|----------|
| Extended drain (max) | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |
|-----------------------------|-----------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> |

*Change every 30000 km/ 24 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |
|-----------------------------|-----------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> |

*Change every 15000 km/ 12 months*

**BEVEL GEAR / TRANSFERBOX**  
Capacity: 0,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |
|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Check every 60000 km/ 24 months*

**DIFFERENTIAL REAR** OBS  
Capacity: 0,95 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |
|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Check every 60000 km/ 24 months*

**TRANSAXLE MANUAL** 02Q 6/1  
Capacity: 2,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| <b>SP Gear 1081</b>      | <b>SP Gear 5015</b>      |

*Check every 48 months/ 60000 km*

# VOLKSWAGEN (VW) (EU) PASSAT CC 357

## PASSAT CC 2.0 TDI (103 KW) 4MOTION

### (2009-2010)



**TRANSAXLE SEMI-AUTOMATIC** DSG 02E (DQ250) 6/1  
Capacity: 7,2 liter (Initial fill), Capacity: 5,2 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 2072**

*Change every 60000 km*

#### HALDEX-CLUTCH

Capacity: 0,72 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 6036**

*Check every 60000 km/ 24 months*

#### HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

*Change every 24 months*

#### COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 12 EVO**

*Check every 48 months/ 60000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*