Change every 15000 km/ 12 months

VOLKSWAGEN (VW) (EU) POLO IV 9N POLO 1.4 16V (55 KW) (2002-2005)



USE Extended drain (max) PRODUCT RECOMMENDATION 1 Helar SP LL-03 0W-30 Change every 30000 km/ 24 months USE Normal PRODUCT RECOMMENDATION 2 Helar SP LL-03 5W-30 CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Helar SP LL-03 0W-30 Helar SP LL-03 5W-30 Change every 45000 km/ 42 months
PRODUCT RECOMMENDATION 2 Helar SP LL-03 0W-30 Change every 30000 km/ 24 months USE Normal PRODUCT RECOMMENDATION 2 Helar SP LL-03 5W-30 CLIMATE Moderate PRODUCT RECOMMENDATION 2 Helar SP LL-03 0W-30 Helar SP LL-03 5W-30 Helar OW-40
Helar SP LL-03 0W-30 Change every 30000 km/ 24 months USE Normal PRODUCT RECOMMENDATION 1 Helar SP LL-03 5W-30 Helar SP LL-03 0W-30 Helar SP LL-03 5W-30 Helar OW-40
Change every 30000 km/ 24 months USE Normal PRODUCT RECOMMENDATION 1 Helar SP LL-03 0W-30 CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar OW-40
USE Normal PRODUCT RECOMMENDATION 1 Helar SP LL-03 0W-30 PRODUCT RECOMMENDATION 2 Helar SP LL-03 5W-30 PRODUCT RECOMMENDATION 3 Helar OW-40
Normal PRODUCT RECOMMENDATION 1 Helar SP LL-03 0W-30 Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar SP LL-03 5W-30 Helar 0W-40
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar SP LL-03 0W-30 Helar SP LL-03 5W-30 Helar 0W-40
Helar SP LL-03 0W-30 Helar SP LL-03 5W-30 Helar 0W-40
Change over 45000 km/ 40 months
Change every 15000 km/ 12 months
USE CLIMATE
Normal Cold
PRODUCT RECOMMENDATION 1
Presteza MSP 5W-30

TRANSAXLE AUTOMATIC 001 4/ Capacity: 5,7 liter	/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	
Check every 24 months/ 30000 km	•	'

TRANSAXLE MANUAL 02T 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 24 months/ 30000 km	'	

VOLKSWAGEN (VW) (EU) POLO IV 9N POLO 1.4 16V (55 KW) (2002-2005)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 1,15 liter	ABS	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 30000 km/24 months, change every 24 months

ELECTRO-HYDRAULIC POWER STEERING		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Check every 24 months/ 30000 km	<u> </u>	

COOLING SYSTEM Capacity: 4,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 12 EVO	
Check every 24 months/ 30000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.