VOLKSWAGEN (VW) (EU) SCIROCCO SCIROCCO 1.8 GT (1986-1992)



PRODUCT RECOMMENDATION 1 Presteza MSP 5W-30	PRODUCT RECOMMENDATION 2 Specialsynth MSP 5W-40	PRODUCT RECOMMENDATION 3 Emperol 5W-40		
Normal		Moderate		
USE		CLIMATE		
ENGINE DX Capacity: 4 liter, Filter capacity: 0,5 liter				

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 5/1 Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Check every 15000 km/ 12 months	'	'

HYDRAULIC BRAKE SYSTEM			
use Normal		CLIMATE	
		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 24 months	•		

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM Capacity: 6,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.