## **VOLKSWAGEN (VW) (EU) TOURAN 1T2** TOURAN 1.4 16V TSI (125 KW) (2008-2010)



<b>ENGINE</b> CAVB, CTHB Capacity: 3,6 liter		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	
Change every 30000 km/ 24 months	s	,

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

Change every 15000 km/ 12 months

TRANSAXLE SEMI-AUTOMATIC DSG 0AM (DQ200) 7/1 Capacity: 1,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		
Check every 48 months/ 60000 km	)		

Check every 48 months/ 60000 km

HYDRAULIC ACTUATION GEARBOX Capacity: 0,9 liter		
CLIMATE		
Moderate		

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	

PRODUCT RECOMMENDATION

## VOLKSWAGEN (VW) (EU) TOURAN 1T2 TOURAN 1.4 16V TSI (125 KW) (2008-2010)



COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Coolant SP 12 EVO			
Check every 48 months/ 60000 km			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.