

**VOLVO (EU) 400 440 1.7i (1991-1995)****ENGINE B18 E**

Capacity: 5 liter (Service fill), Filter capacity: 0,5 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Emperol 5W-40</b>     | <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    |

*Change every 15000 km/ 12 months*

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Severe                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>HDX 20W-50</b>        |  |               |

*Change every 7500 km/ 6 months*

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Severe                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Bi-Turbo 15W-40</b>   |  |          |

*Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC ZF 4/1**

Capacity: 5,5 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

*Check every 15000 km/ 12 months, change every 45000 km/ 36 months***TRANSAXLE MANUAL 5/1**

Capacity: 3,4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Gear 5015</b>      |  |          |

*Check every 15000 km/ 12 months*

**VOLVO (EU) 400 440 1.7i (1991-1995)****HYDRAULIC BRAKE SYSTEM**

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

*Change every 30000 km/ 24 months*

**POWER STEERING**

Capacity: 0,7 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF-F (Ford)</b>      |  |          |

*Check every 15000 km/ 12 months*

**COOLING SYSTEM**

Capacity: 7 liter

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

*Change every 30000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*