## VOLVO (EU) 400 460 1.7 (1991-1993)



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40
Change every 15000 km/ 12 month	es .	
JSE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 20W-50		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 15W-40		

TRANSAXLE AUTOMATIC ZF 4/1 Capacity: 3,3 liter			
use Normal		сымате Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			
Check every 15000 km/ 12 months	shange every 45000 km/ 36 months		

TRANSAXLE MANUAL 5/1 Capacity: 3,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Check every 15000 km/ 12 months	

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 30000 km/24 months		1

## VOLVO (EU) 400 460 1.7 (1991-1993)



POWER STEERING Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF-F (Ford)	
Check every 15000 km/ 12 months	

COOLING SYSTEM Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 30000 km/24 months	<u>'</u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.