

VOLVO (EU) 700 740 B230F (1985-1992)**ENGINE B230F**

Capacity: 3,85 liter, Filter capacity: 0,5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**HDX 20W-50***Change every 10000 km/ 6 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Emperol 10W-40****PRODUCT RECOMMENDATION 2****Bi-Turbo 15W-40****PRODUCT RECOMMENDATION 3****Asyntho 5W-30***Change every 10000 km/ 6 months***USE**

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**HDX 20W-50***Change every 5000 km/ 3 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Emperol 10W-40****PRODUCT RECOMMENDATION 2****Bi-Turbo 15W-40****PRODUCT RECOMMENDATION 3****Asyntho 5W-30***Change every 5000 km/ 3 months***DIFFERENTIAL REAR**

Capacity: 1,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90***Check every 10000 km/ 6 months***USE**

First change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90***Change every 10000 km/ 6 months*

VOLVO (EU) 700 740 B230F (1985-1992)**TRANSMISSION AUTOMATIC** Aisin Warner 3/1

Capacity: 6,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D***Check every 6 months, change every 40000 km***TRANSMISSION AUTOMATIC** ZF 4/1

Capacity: 6 liter, Capacity: 7,5 liter (Dry fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D***Check every 6 months, change every 40000 km***TRANSMISSION MANUAL** M47 5/1

Capacity: 1,55 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF-F (Ford)***Check every 10000 km/ 6 months***TRANSMISSION MANUAL + OVERDRIVE** M46 5/1

Capacity: 2,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF-F (Ford)***Check every 10000 km/ 6 months***USE**

First change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF-F (Ford)***Change every 10000 km/ 6 months*

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 12 months***POWER STEERING**

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF-A	ATF-F (Ford)	

*Check every 10000 km/ 6 months***COOLING SYSTEM**

Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.