VOLVO (EU) 900 960 3.0 24V B6304G (1991-1996)



ENGINE B6304G Capacity: 5,75 liter, Capacity: 6,15	liter (Dry fill), Filter capacity: 0,5 liter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40
Change every 15000 km/ 12 month	IS	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40
	1	1

Change every 7500 km/ 6 months

DIFFERENTIAL REAR Capacity: 1,3-1,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	
Check every 15000 km/ 12 months	•

TRANSMISSION AUTOMATIC AW30-43 Capacity: 7,5 liter	/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 15000 km/ 12 months

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Change every 75000 km

VOLVO (EU) 900 960 3.0 24V B6304G (1991-1996)



TRANSMISSION MANUAL 5/1 Capacity: 2,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF-F (Ford)	

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,65 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
	3	

Change every 24 months

POWER STEERING Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF-A	ATF-F (Ford)	

Check every 15000 km/ 12 months, change every 24 months

COOLING SYSTEM Capacity: 8,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.