HYDRAULIC BRAKE/CLUTCH SYSTEM

VOLVO (EU) C30 C30 D2 (2010-2013)



ENGINE D4162T Capacity: 3,9 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Duranza LSP 5W-30				
Change every 20000 km/ 12 months				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Presteza MSP 0W-30				
Change every 20000 km/ 12 months				

TRANSAXLE MANUAL B6 6/1 Capacity: 1,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Check every 20000 km, change every 40000 km/24 months	
USE	CLIMATE
Severe	Moderate
Severe	Woderate
PRODUCT RECOMMENDATION 1	Moderate
	Moderate

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

VOLVO (EU) C30 C30 D2 (2010-2013)



COOLING SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 18	
Check every 20000 km/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.