## **VOLVO (EU) S40 S40 1.9 D (85 KW)** (2002-2004)



<b>ENGINE</b> D4192T3 Capacity: 5,6 liter, Filter capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

Change every 15000 km/ 12 months

TRANSAXLE MANUAL M56 5/1 Capacity: 2,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,4-0,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Charle grant 15000 (m/ 12 months, change grant 24 months)		

Check every	′ 15000 km/	12 months,	change	every 24	months
-------------	-------------	------------	--------	----------	--------

POWER STEERING Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Almirol	ATF Dexron II-D	
Check every 15000 km/ 12 months		

USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 15000 km/ 12 months	

## **VOLVO (EU) S40 S40 1.9 D (85 KW)** (2002-2004)



COOLING SYSTEM Capacity: 6,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Chack avery 15000 km/ 12 months	

Check every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.