## **VOLVO (EU) S40 S40 1.9 TD** (1995-1999)



<b>ENGINE</b> D4192T Capacity: 5 liter, Filter capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 10W-40	Bi-Turbo 15W-40	
Change every 15000 km/ 12 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 5W-40	Asyntho 5W-30	
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 15W-40		
Change every 7500 km/ 6 months		

TRANSAXLE MANUAL M5D 5/1 Capacity: 3,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 15000 km/ 12 months, change every 105000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		

Change every 45000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,4-0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	

**SP Gear 5015** 

## VOLVO (EU) S40 S40 1.9 TD (1995-1999)



POWER STEERING Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Almirol	ATF Dexron II-D	
01 1 450001 (40 4		-

Check every 15000 km/ 12 months

CLIMATE
Moderate

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.