

VOLVO (EU) S80 S80 2.0 (2010-2011)

ENGINE B4204S3
Capacity: 4,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30*Change every 30000 km/ 12 months*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-30*Change every 30000 km/ 12 months*

TRANSAXLE MANUAL MTX75 6/1
Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

TRANSAXLE SEMI-AUTOMATIC MPS6 (Getrag 6 DCT450) 6/1
Capacity: 5,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072*Check every 20000 km/ 12 months*

VOLVO (EU) S80 S80 2.0 (2010-2011)**HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Check every 30000 km/ 12 months, change every 60000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 30000 km/ 12 months***POWER STEERING**

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013*Check every 12 months/ 30000 km***COOLING SYSTEM**

Capacity: 7,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 18*Check every 12 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.