VOLVO (EU) XC60 XC60 2.0T (149 KW) (2010-2012)



ENGINE B4204T6 Capacity: 4,1-5,4 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		
Change every 30000 km/ 12 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-30		
Change every 30000 km/ 12 months		

Change every 30000 km/ 12 months

TRANSAXLE SEMI-AUTOMATIC MPS6 (Getrag 6 DCT450) 6/1 Capacity: 5,6-7,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 2072			
Check every 12 months/ 30000 km			

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 12 months

POWER STEERING Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 12 months/ 30000 km	

VOLVO (EU) XC60 XC60 2.0T (149 KW) (2010-2012)



COOLING SYSTEM Capacity: 10,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 18		
Charles ware 12 marths (2000) lim		

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.