

VOLVO (EU) XC60 XC60 2.4D (120 KW) AWD (2010-2011)



ENGINE D5244T16
Capacity: 5,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-30

Change every 30000 km/ 12 months

BEVEL GEAR TRANSFERBOX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

TRANSAXLE AUTOMATIC TF-80SC/SDAWD 6/1
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Change every 60000 km/ 24 months

VOLVO (EU) XC60 XC60 2.4D (120 KW) AWD (2010-2011)


TRANSAXLE MANUAL M66-AWD 6/1

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		

HALDEX-CLUTCH

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 6033		

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 30000 km/ 12 months, change every 60000 km/ 24 months

POWER STEERING

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 12 months/ 30000 km

COOLING SYSTEM

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 18		

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.