

# INTERNATIONAL HARVESTER 55 / 56 955

(1978-1981)



**ENGINE D-310**  
Capacity: 12 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Check every 10 hours, change every 200 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SCD 20W-20***Check every 10 hours, change every 200 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Check every 10 hours, change every 200 hours***DIFFERENTIAL FRONT**

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 200 hours, change every 800 hours***HUB REDUCTIONS FRONT**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 200 hours, change every 800 hours*

# INTERNATIONAL HARVESTER 55 / 56 955

## (1978-1981)



### HUB REDUCTIONS REAR

Capacity: 7 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

Check every 800 hours, change every 1600 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

Check every 800 hours, change every 1600 hours

### TRANSAXLE MANUAL 12/4

Capacity: 42 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

Check every 200 hours, change every 1600 hours

### HYDRAULIC SYSTEM

Capacity: 34 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

Check every 50 hours, change every 800 hours

### HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

Check every 50 hours, change every 1600 hours

# INTERNATIONAL HARVESTER 55 / 56 955

## (1978-1981)



### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 50 hours*

### GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 1600 hours*

### COOLING SYSTEM

Capacity: 23,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 50 hours, change every 1200 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*