

ABARTH 500C / 595C / 695C 312 500C 1.4 T-JET (118 KW) (2009-2016)

**ENGINE 312A1000**

Capacity: 2,9 liter (Service fill), Filter capacity: 0,15 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Emperol 5W-50*Change every 15000 km/ 12 months*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

Emperol 5W-50*Check every 3000 km, change every 10000 km/ 12 months***TRANSAXLE MANUAL C 514 R 5/1**

Capacity: 1,65 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear 5015**HYDRAULIC BRAKE SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 30000 km, change every 60000 km/ 24 months***COOLING SYSTEM**

Capacity: 5,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.