

# ABARTH 500C / 595C / 695C 312 595/695C

## 1.4 T-JET (132 KW) (2016-2023)



**ENGINE** 312A3000 / 312B3000  
Capacity: 2,9-3,1 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Emperol 5W-50**

*Check every 3000 km, change every 15000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**Emperol 5W-50**

*Check every 3000 km, change every 10000 km/ 12 months*

**TRANSAXLE MANUAL** 5/1  
Capacity: 1,55 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1081**

PRODUCT RECOMMENDATION 2

**SP Gear 5015**

*Change every 30000 km/ 24 months*

**TRANSAXLE SEMI-AUTOMATIC** 5/1  
Capacity: 1,55 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1081**

PRODUCT RECOMMENDATION 2

**SP Gear 5015**

*Change every 30000 km/ 24 months*

**HYDRAULIC ACTUATION GEARBOX**  
Capacity: 0,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3023**

*Check every 24 months/ 30000 km*

# ABARTH 500C / 595C / 695C 312 595/695C

## 1.4 T-JET (132 KW) (2016-2023)



### HYDRAULIC BRAKE SYSTEM

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Change every 24 months

### COOLING SYSTEM

Capacity: 5,2 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

Check every 3000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.