ACURA (USA / CAN) RLX RLX 3.5 I-VTEC V6 HYBRID (USA) (2015-2020)



USE	CLIMATE	
Flexible (on board maintenance system)	Moderate	
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
	·	
DIFFERENTIAL DEAD Twin Motor Unit		
DIFFERENTIAL REAR Twin Motor Unit Capacity: 2,42 liter		
USE	CLIMATE	
use Severe	climate Moderate	
use Severe PRODUCT RECOMMENDATION 1		
Severe		
Severe PRODUCT RECOMMENDATION 1		
Severe PRODUCT RECOMMENDATION 1 SP Matic 4036		
Severe PRODUCT RECOMMENDATION 1 SP Matic 4036 Change every 15000 miles	Moderate	
Severe PRODUCT RECOMMENDATION 1 SP Matic 4036 Change every 15000 miles USE	Moderate	

USE

Flexible (on board maintenance system)

PRODUCT RECOMMENDATION 1

SP Matic 4036

CLIMATE

Moderate

ACURA (USA / CAN) RLX RLX 3.5 I-VTEC V6 HYBRID (USA) (2015-2020)



TRANSMISSION AUTOMATIC DCT 7/1 Capacity: 3,5 liter	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 25000 miles	
USE	CLIMATE
Severe, first change only	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 30000 miles	
USE	CLIMATE
Flexible (on board maintenance sys	rem) Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 36 months	
COOLING SYSTEM	
Capacity: 7,9 liter (Service fill)	CLIMATE

COOLING SYSTEM INVERTER Capacity: 1,23 liter	
USE	CLIMATE
Flexible (on board maintenance system)	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

Flexible (on board maintenance system)

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Moderate

PRODUCT RECOMMENDATION

ACURA (USA / CAN) RLX RLX 3.5 I-VTEC V6 HYBRID (USA) (2015-2020)



AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 455-505 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.