PRODUCT RECOMMENDATION

ACURA (USA / CAN) RLX RLX 3.5 I-VTEC V6 HYBRID (USA) (2015-2020)



ENGINE JNB1 Capacity: 4,3 liter (Service fill), Filter capacity: 0,3 liter		
USE		CLIMATE
Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		

DIFFERENTIAL REAR Twin Motor Unit Capacity: 2,42 liter	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 15000 miles	

use Severe, first change only	climate Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
SP Matic 4036	

SP Matic 4036		
PRODUCT RECOMMENDATION 1		
Flexible (on board maintenance syste	em)	Moderate
USE		CLIMATE
Change every 7500 miles		

ACURA (USA / CAN) RLX RLX 3.5 I-VTEC V6 HYBRID (USA) (2015-2020)



TRANSMISSION AUTOMATIC DCT 7/1 Capacity: 3,5 liter		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Change every 25000 miles		
USE		CLIMATE
Severe, first change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Change every 30000 miles		
USE		CLIMATE
Flexible (on board maintenance systemeters)	em)	Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 36 months	

COOLING SYSTEM Capacity: 7,9 liter (Service fill)		
USE		CLIMATE
Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
I RODOCT RECOMMENDATION I		

COOLING SYSTEM INVERTER Capacity: 1,23 liter		
USE		CLIMATE
Flexible (on board maintenance systemeters)	em)	Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

ACURA (USA / CAN) RLX RLX 3.5 I-VTEC V6 HYBRID (USA) (2015-2020)



AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 455-505 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.