ALFA ROMEO (EU) GIULIETTA 940 GIULIETTA 1.6 JTDM (88 KW) (2015-2018)



ENGINE 940C1000 Capacity: 4,2 liter (Service fill)	
USE	CLIMATE
Severe, flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Avanza MSP 0W-30	
Change every 12 months	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Avanza MSP 0W-30	
Change every 35000 km/ 24 months	

TRANSAXLE MANUAL 6/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 35000 km	,	

TRANSAXLE SEMI-AUTOMATIC TCT 6/1			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		
Check every 30000 km	'	'	

HYDRAULIC ACTUATION GEARBOX		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		
Check every 30000 km	·	

ALFA ROMEO (EU) GIULIETTA 940 GIULIETTA 1.6 JTDM (88 KW) (2015-2018)



HYDRAULIC BRAKE/CLUTCH SYST Capacity: 0,8 liter	EM ABS		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 35000 km/ 24 months		·	

COOLING SYSTEM Capacity: 6,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 35000 km	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.