

ALFA ROMEO (EU) SPIDER 115 ALFA SPIDER 1.6 (1990-1993)

**ENGINE**

Capacity: 6,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40*Check every 500 km, change every 20000 km/ 12 months***DIFFERENTIAL REAR (4x2)**

Capacity: 1,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 20000 km, change every 40000 km/ 24 months***TRANSMISSION MANUAL 5/1**

Capacity: 1,85 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 20000 km, change every 40000 km/ 24 months***HYDRAULIC BRAKE SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 12 months***HYDRAULIC CLUTCH SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 12 months*

ALFA ROMEO (EU) SPIDER 115 ALFA SPIDER 1.6 (1990-1993)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 500 km		

GREASE POINTS/NIPPLES PROPELLER SHAFT SLIDING JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
Check every 20000 km/ 12 months		

COOLING SYSTEM

Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Check every 500 km, change every 60000 km/ 24 months		

STEERING BOX

Capacity: 0,14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
Check every 20000 km/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.