ALFA ROMEO (EU) SPIDER 916 SPIDER 2.0 16V TWIN SPARK (1995-2006)



| ENGINE AR 16201 Capacity: 4,4 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Emperol Racing 10W-60 | Emperol 10W-40 | |
| Check every 500 km, change every 2000 | 00 km/ 12 months | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Duranza LSP 5W-30 | Asyntho 5W-30 | |
| Check every 500 km, change every 2000 | 00 km/ 12 months | |

| TRANSAXLE MANUAL 5/1 Capacity: 2 liter | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Gear 5015 | Gearlube GL-4 80W | | |
| Check every 80000 km/ 48 months | · | | |

| HYDRAULIC SYSTEM (ROOF) ELECTRONIC/HYDRAULIC Capacity: 0,6 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Fluid 3013 | | |
| Check every 20000 km/ 12 months | | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| Check every 500 km, change every 60000 km/24 months | | |

ALFA ROMEO (EU) SPIDER 916 SPIDER 2.0 16V TWIN SPARK (1995-2006)



| POWER STEERING Capacity: 1,3 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| ATF Dexron II-D | |
| Check every 500 km | |

| COOLING SYSTEM Capacity: 8,4 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |
| | |

Check every 500 km, change every 60000 km/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.