

# ALFA ROMEO (EU) STELVIO 949 STELVIO

## 2.2 JTD (132 KW) ADBLUE (2017-2018)

**ENGINE**

Capacity: 3,9-4,4 liter (Service fill)

**USE**

Flexible (max)

**CLIMATE**

Moderate

PRODUCT RECOMMENDATION 1

**Presteza MSP 0W-20***Change every 24 months***DIFFERENTIAL RDU 210/215-LSD**

Capacity: 1,1 liter

**USE**

Normal

**CLIMATE**

Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071****DIFFERENTIAL RDU 230-LSD**

Capacity: 0,9 liter

**USE**

Normal

**CLIMATE**

Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071****DIFFERENTIAL REAR RDU 210-eLSD**

Capacity: 1,4 liter

**USE**

Normal

**CLIMATE**

Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071****TRANSMISSION AUTOMATIC 8/1**

Capacity: 9,1 liter

**USE**

Normal

**CLIMATE**

Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2034**

# ALFA ROMEO (EU) STELVIO 949 STELVIO

## 2.2 JTD (132 KW) ADBLUE (2017-2018)



### HYDRAULIC BRAKE SYSTEM

Capacity: 0,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid Racing***Change every 24 months*

### COOLING SYSTEM

Capacity: 8-8,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

### COOLING SYSTEM INTERCOOLER

Capacity: 4,7-5,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

### SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

Capacity: 16,1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*