

ALFA ROMEO (EU) BRERA 939 BRERA 1750 TURBO (2009-2011)

**ENGINE** 939B1000

Capacity: 5 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Specialsynth MSP 5W-40*Change every 35000 km***TRANSAXLE MANUAL** 6/1

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 35000 km***GEAR OPERATING SYSTEM** Selespeed

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 35000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 35000 km/ 24 months***POWER STEERING**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013*Check every 35000 km*

ALFA ROMEO (EU) BRERA 939 BRERA 1750 TURBO (2009-2011)

**COOLING SYSTEM**

Capacity: 6,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12****PRODUCT RECOMMENDATION 3****Coolant -38 Organic NF***Check every 35000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.