

# ALFA ROMEO (EU) SPIDER 939 SPIDER 2.4 JTDM 20V (154 KW) (2008-2010)



**ENGINE** 939A9000  
Capacity: 6,4 liter

| USE            | CLIMATE  |
|----------------|----------|
| Flexible (max) | Moderate |

PRODUCT RECOMMENDATION 1

**Emperol 5W-40**

*Change every 35000 km*

**TRANSAXLE MANUAL** 6/1  
Capacity: 2,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 5015**

*Check every 35000 km*

## HYDRAULIC SYSTEM (ROOF) ELECTRONIC/HYDRAULIC

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3013**

*Check every 35000 km*

## HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

*Change every 35000 km/ 24 months*

## POWER STEERING

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3013**

*Check every 35000 km*

# ALFA ROMEO (EU) SPIDER 939 SPIDER 2.4 JTDM 20V (154 KW) (2008-2010)

**COOLING SYSTEM**

Capacity: 7,35 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

Check every 35000 km

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*