

**AUDI (EU) 100, S4 100 2.8E (1990-1992)****ENGINE**

Capacity: 5 liter, Filter capacity: 0,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Helar SP LL-03 5W-30****PRODUCT RECOMMENDATION 2****Specialsynth MSP 5W-40****PRODUCT RECOMMENDATION 3****Emperol 5W-40***Change every 15000 km/ 12 months***USE**

Normal

**CLIMATE**

Arctic

**PRODUCT RECOMMENDATION 1****Presteza MSP 5W-30***Change every 15000 km/ 12 months***DIFFERENTIAL FROM AUTOMATIC**

Capacity: 0,7 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90***Check every 15000 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,35 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90***Check every 15000 km/ 12 months***TRANSMISSION AUTOMATIC 01K 4/1**

Capacity: 2,7 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****ATF Dexron II-D***Change every 30000 km/ 24 months*

**AUDI (EU) 100, S4 100 2.8E (1990-1992)****HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 24 months*

**POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

**COOLING SYSTEM**

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*