

# AUDI (EU) 80, RS 2 80 QUATTRO 2.3E (1992-1995)



## ENGINE NG

Capacity: 4 liter, Filter capacity: 0,5 liter

| USE                         |                             | CLIMATE                  |
|-----------------------------|-----------------------------|--------------------------|
| Normal                      |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> | <b>Helar 0W-40</b>       |

Change every 15000 km/ 12 months

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Presteza MSP 5W-30</b> |  |         |

Change every 15000 km/ 12 months

## DIFFERENTIAL REAR

Capacity: 1,3 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Gearlube GL-5 80W-90</b> |  |          |

Check every 15000 km/ 12 months

## TRANSAXLE MANUAL/TRANSFERBOX 5/1

Capacity: 2,85 liter

| USE                      |                           | CLIMATE  |
|--------------------------|---------------------------|----------|
| Normal                   |                           | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |          |

Check every 15000 km/ 12 months

## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Change every 24 months

**AUDI (EU) 80, RS 2 80 QUATTRO 2.3E (1992-1995)****POWER STEERING**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 3013</b>     |  |          |

**COOLING SYSTEM**

Capacity: 8,5 liter

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*