Change every 15000 km/ 12 months

AUDI (EU) A4, S4, RS 4 8E A4 1.9 TDI (85 KW) DPF (2006-2008)



ENGINE BRB Capacity: 3,8 liter (Service fill)		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	
Change every 30000 km/ 24 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

TRANSAXLE MANUAL 012 / 01W / 0A9 5/1 Capacity: 2,35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 24 months/ 30000 km		

TRANSAXLE MANUAL 01X 6/1 Capacity: 3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Check every 24 months/ 30000 km	

HYDRAULIC BRAKE/CLUTCH SYSTEM USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	'

AUDI (EU) A4, S4, RS 4 8E A4 1.9 TDI (85 KW) DPF (2006-2008)



POWER STEERING		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Check every 24 months/ 30000 km	·	

COOLING SYSTEM Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 12 EVO	
Check every 24 months/ 30000 km	,	-

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.