

PRODUCT RECOMMENDATION

# AUDI (EU) A4, S4, RS 4 8E A4 2.7 TDI V6 (132 KW) DPF (2006-2008)



## ENGINE BPP Capacity: 8,2 liter

| USE                         |                             | CLIMATE  |
|-----------------------------|-----------------------------|----------|
| Extended drain (max)        |                             | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |          |
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> |          |

Change every 30000 km/ 24 months

| USE                         |                             | CLIMATE  |
|-----------------------------|-----------------------------|----------|
| Normal                      |                             | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |          |
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> |          |

Change every 15000 km/ 12 months

## DIFFERENTIAL CVT Capacity: 1,3 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Gear 1071</b>      |  |          |

## TRANSAXLE MANUAL 0A2 6/1

| USE                      |                           | CLIMATE  |
|--------------------------|---------------------------|----------|
| Normal                   |                           | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |          |

Check every 24 months/ 30000 km

## TRANSMISSION CVT 0AN 1/1 Capacity: 7,5 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4016</b>     |  |          |

# AUDI (EU) A4, S4, RS 4 8E A4 2.7 TDI V6 (132 KW) DPF (2006-2008)



## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4***Change every 24 months*

## POWER STEERING

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3013***Check every 24 months/ 30000 km*

## COOLING SYSTEM

Capacity: 12 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 12**

PRODUCT RECOMMENDATION 2

**Coolant SP 12 EVO***Check every 24 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.