AUDI (EU) A4, S4, RS 4 8E A4 1.9 TDI (85 KW) (2004-2006)



ENGINE BKE (PD) Capacity: 3,6 liter (Service fill)			
use Extended drain (max)		сцімате Moderate	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30		
Change every 30000 km/ 24 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Specialsynth MSP 5W-40	

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 012 / 01W / 0A9 5/1 Capacity: 2,25 liter					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
SP Gear 1011	Syngear TDL 75W-90				
Check every 24 months/ 30000 km	· · · ·	I			

HYDRAULIC BRAKE/CLUTCH SYSTEM

HYDRAULIC BRAKE/CLUTCH SYSTEM				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Drauliquid-LV Super DOT 4				
Charge avery 24 marths				

Change every 24 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 24 months/ 30000 km	· · · ·

AUDI (EU) A4, S4, RS 4 8E A4 1.9 TDI (85 KW) (2004-2006)



COOLING SYSTEM Capacity: 8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 12	Coolant SP 12 EVO		

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.