

AUDI (EU) A4, S4, RS 4 8W S4 3.0 TFSI QUATTRO (260 KW) (2016 AND AFTER)



ENGINE CWGD
Capacity: 7,25 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar FE LL-04 0W-20

DIFFERENTIAL FROM AUTOMATIC

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

DIFFERENTIAL REAR 0D3

Capacity: 0,95 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

DIFFERENTIAL REAR 0G2

Capacity: 0,85 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR OUTER SECTIONS 0D3

Capacity: 0,93 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

TRANSFERBOX FROM AUTOMATIC

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

AUDI (EU) A4, S4, RS 4 8W S4 3.0 TFSI QUATTRO (260 KW) (2016 AND AFTER)



TRANSMISSION AUTOMATIC 0D5 8/1

Capacity: 8,6-9 liter (Dry fill), Capacity: 3,6-4 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2034		

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

COOLING SYSTEM BEFORE MODEL YEAR 2019

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 24 months/ 30000 km

COOLING SYSTEM MODEL YEAR 2019 AND LATER

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.