## **HYUNDAI (EU) I30 FD I30 1.6 CRDI VGT DPF (85 KW)** (2010-2012)



| JSE  |                          | CLIMATE                  |
|--|--------------------------|--------------------------|
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                             | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar SP LL-03 5W-30                                 | Presteza MSP 5W-30       | Meganza MSP 5W-30        |
| Change every 30000 km/ 12 months                     |                          |                          |
| JSE  |                          | CLIMATE                  |
| Normal   |                          | Cold                     |
| PRODUCT RECOMMENDATION 1                             |                          |                          |
| Helar SP LL-03 0W-30                                 |                          |                          |
| Change every 30000 km/ 12 months                     |                          |                          |
| JSE  |                          | CLIMATE                  |
| Severe   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                             | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar SP LL-03 5W-30                                 | Presteza MSP 5W-30       | Meganza MSP 5W-30        |
| Change every 15000 km/ 6 months                      |                          |                          |
| JSE  |                          | CLIMATE                  |
| Severe   |                          | Cold                     |
| PRODUCT RECOMMENDATION 1                             |                          |                          |
| Helar SP LL-03 0W-30                                 |                          |                          |
| Change every 15000 km/ 6 months                      |                          |                          |
|  |                          |                          |
| TRANSAXLE AUTOMATIC A4CF2 4/1<br>Capacity: 6,6 liter |                          |                          |
| JSE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                             |                          |                          |
| SP Matic 4026  |                          |                          |
| Check every 48 months/ 60000 km                      |                          |                          |
| JSE  |                          | CLIMATE                  |
| Severe   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                             |                          |                          |
|  |                          |                          |

## **HYUNDAI (EU) I30 FD I30 1.6 CRDI VGT DPF (85 KW)** (2010-2012)



| TRANSAXLE MANUAL M5CF3 5/1 Capacity: 2 liter |                          |          |  |  |
|--|--------------------------|----------|--|--|
| USE  |                          | CLIMATE  |  |  |
| Normal                                       |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2 |          |  |  |
| SP Gear 5015                                 | Syngear 75W-90           |          |  |  |
| Check every 48 months/ 60000 km              | 1                        |          |  |  |
| USE  |                          | CLIMATE  |  |  |
| Severe                                       |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2 |          |  |  |
| SP Gear 5015                                 | Syngear 75W-90           |          |  |  |
| Change every 120000 km                       |                          |          |  |  |

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,7-0,8 liter |                          |                          |  |  |
|---|--------------------------|--------------------------|--|--|
| use<br>Normal   |                          | CLIMATE                  |  |  |
|   |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1                              | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |  |
| Drauliquid-LV Super DOT 4                             | Drauliquid-S DOT 4       | Drauliquid DOT 3         |  |  |
| Change every 30000 km/24 months                       | •                        | •                        |  |  |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| Capacity: 6,8 liter              |                          |          |  |  |
|----------------------------------|--------------------------|----------|--|--|
| USE                              |                          | CLIMATE  |  |  |
| Normal                           |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |          |  |  |
| Coolant SP 15+                   | Coolant SP 12            |          |  |  |
| Change every 30000 km/ 24 months |                          |          |  |  |
| USE                              |                          | CLIMATE  |  |  |
| First change only                |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |          |  |  |
| Coolant SP 15+                   | Coolant SP 12            |          |  |  |

Change every 210000 km/ 120 months

**COOLING SYSTEM** 

PRODUCT RECOMMENDATION

## HYUNDAI (EU) 130 FD 130 1.6 CRDI VGT DPF (85 KW) (2010-2012)



## AIRCONDITIONING COMPRESSOR

Capacity: 150 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.